



SAFETY DATA SHEET

Version 1.1
Print Date 03/15/2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Lithium
Brand : Accurate Atom
SKU-No. : EB-24002
CAS-No. : 7439-93-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances
Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Accurate Atom Inc.
1425 W. Lincoln HWY
DeKalb, Illinois, 60115
www.accurateatom.com
Tech@accurateatom.com

1.4 Emergency telephone

Accurate Atom Emergency Telephone: (630) 659-5999

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Chemicals which, in contact with water, emit flammable gases (Category 1), H260
Skin corrosion (Category 1B), H314
Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H260

In contact with water releases flammable gases which may ignite spontaneously.

H314

Causes severe skin burns and eye damage.

Precautionary Statements

P223

Do not allow contact with water.

P231 + P232

Handle under inert gas. Protect from moisture.

P260

Do not breathe dust.

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 +

P310

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P335 + P334

Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.

P363

Wash contaminated clothing before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P402 + P404

Store in a dry place. Store in a closed container.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : Li
Molecular weight : 6.94 g/mol
CAS-No. : 7439-93-2
EC-No. : 231-102-5
Index-No. : 003-001-00-4

Component	Classification	Concentration
-----------	----------------	---------------

lithium		
	Water-react 1; Skin Corr. 1B; Eye Dam. 1; H260, H314, H318	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

No data available

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing media: sodium chloride/hydrogen carbonate or lime stone. Special powder against metal fire

Unsuitable extinguishing media

Foam Water

5.2 Special hazards arising from the substance or mixture

Lithium oxides
Not combustible.

5.3 Advice for firefighters

No data available

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8.

6.2 Environmental precautions

No data available

6.3 Methods and materials for containment and cleaning up

No data available

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store under argon. Handle under argon.

Storage class

Storage class (TRGS 510): 4.3: Hazardous materials, which set free flammable gases upon contact with water

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Control of environmental exposure

Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: chips
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 180 °C (356 °F) - lit.
f) Initial boiling point and boiling range	1,342 °C 2,448 °F - lit.
g) Flash point	()Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapor pressure	1 hPa at 723 °C (1333 °F)
l) Vapor density	No data available
m) Density	0.534 g/cm ³ at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	Risk of violent reaction.
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Reacts violently with water.

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Water

Acids

Halogenated hydrocarbon

Carbon dioxide (CO₂)

boron trifluoride

halogen-halogen compounds

chromyl chloride

chromium(VI) oxide

Boranes

Fluorine

halogen compounds

carbon dioxide

phosphorus

platinum

Mercury

Rust

Nitric acid

nitrogen

Sulfides

metallic oxides

sodium carbonate

Hydrogen

Risk of explosion with:

nitrogen

halogens

sulfur

Bromine

Bromoform

Chlorine

Chloroform

Diazonium compounds

dichloromethane

Halogenated hydrocarbon

iodine

methyl iodine

Peroxides

mineral acids

Oxygen

tetrachloromethane

thionyl chloride

trichloroethene
sulphur dioxide
Sulphuric acid
silver salt
Carbon monoxide
with
Water
Water
with
Powdered metals

10.4 Conditions to avoid

Reacts with water to generate Hydrogen gas.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral: No data available

Inhalation: No data available

Dermal: No data available

LD50 Intraperitoneal - Mouse - 1,000 mg/kg

Skin corrosion/irritation

Remarks: No data available

Serious eye damage/eye irritation

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: OJ5540000

Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported. Central nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur. Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result of repeated exposure to lithium ion., Cough, Shortness of breath, Headache, Nausea, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

No data available

SECTION 14: Transport information**DOT (US)**

UN number: 1415 Class: 4.3 Packing group: I
Proper shipping name: Lithium
Reportable Quantity (RQ):
Poison Inhalation Hazard: No

IMDG

UN number: 1415 Class: 4.3 Packing group: I EMS-No: F-G, S-N
Proper shipping name: LITHIUM

IATA

UN number: 1415 Class: 4.3 Packing group: I
Proper shipping name: Lithium
IATA Passenger: Not permitted for transport

SECTION 15: Regulatory information**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard

Massachusetts Right To Know Components

lithium	CAS-No. 7439-93-2	Revision Date 1993-04-24
---------	----------------------	-----------------------------

Pennsylvania Right To Know Components

lithium	CAS-No. 7439-93-2	Revision Date 1993-04-24
---------	----------------------	-----------------------------

SECTION 16: Other information

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 1.1

Print Date: 03/15/2025